RESIDENTIAL ALTERATIONS

CEC-CF1R-ALT-01-E (Revised 09/16)

| | Ŕ |
|------------------------------|-----|
| CALIFORNIA ENERGY COMMISSION | 400 |

| CERTIFICATE OF COMPLIANCE | CF1R-ALT-01-E |
|--------------------------------------|---------------|
| Prescriptive Residential Alterations | (Page 1 of 2) |

| Project Name: | Date Prepared: |
|---------------|----------------|
|---------------|----------------|

| A. G | eneral Information | | | |
|------|--------------------|-----------|---|--|
| 01 | Project Name: | 02 | Date Prepared: | |
| 03 | Project Location: | 04 | 4 Building Front Orientation (deg or cardinal): | |
| 05 | CA City: | 06 | 6 Number of Altered Dwelling Units: | |
| 07 | Zip Code: | 08 | 8 Fuel Type: | |
| 09 | Climate Zone: | 10 | 10 Total Conditioned Floor Area (ft ²): | |
| 11 | Building Type: | 12 | 2 Slab Area (ft ²): | |
| 12 | Project Scope: | ct Scope: | Exceptions to Minimum Aged Solar Reflectance | |
| 13 | Froject Scope. | 14 | and Minimum Thermal Emittance or SRI: | |

| B. Roo | B. Roof Replacement (Section 150.2(b)1H) | | | | | | | | | | | | | |
|--------|--|-------|-----------|---------|---------|------------|---------------|-------------|-----------|------------|-------------|-------------|-----------|------------|
| 01 | 02 | 03 | 04 | 05 | 06 | 07 | 08 | 09 | 10 | 11 | 1 | 2 | 13 | 14 |
| | | | | CRRC | | | | Propo | sed | | | Minimum | Required | |
| | | | | Product | | R-value | | | | | Aged Solar | Aged Solar | | |
| Tag/ | Method of | Roof | | ID | Product | Deck | Initial Solar | Aged Solar | Thermal | SRI | Reflectance | Reflectance | Thermal | SRI |
| ID | Compliance | Pitch | Exception | Number | Type | Insulation | Reflectance | Reflectance | Emittance | (Optional) | (Max) | (Min) | Emittance | (Optional) |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

Notes:

- Roof area covered by building integrated photovoltaic panels and solar thermal panels are exempt from the above Cool Roof requirements.
- Liquid field applied coatings must comply with installation criteria from section 110.8(i)4.

Documentation Author Name:

RESIDENTIAL ALTERATIONS

DOCUMENTATION AUTHOR'S DECLARATION STATEMENT

I certify that this Certificate of Compliance documentation is accurate and complete.

CEC-CF1R-ALT-01-E (Revised 09/16)

| | 1 |
|------------------------------|---------------|
| CALIFORNIA ENERGY COMMISSION | - ENERGY COMM |

| 020 01 111 121 01 2 (11011000 001 10) | CALIFORNIA COMMINICATOR |
|---------------------------------------|-------------------------|
| CERTIFICATE OF COMPLIANCE | CF1R-ALT-01- |
| Prescriptive Residential Alterations | (Page 2 of 2 |
| Project Name: | Date Prepared: |
| | |

Documentation Author Signature:

| Company: | Signature Date: | | | | |
|--|---|--|--|--|--|
| Address: | CEA/ HERS Certification Identification (if applicable): | | | | |
| City/State/Zip: | Phone: | | | | |
| RESPONSIBLE PERSON'S DECLARATION STATEMENT | | | | | |
| designer). That the energy features and performance specifications, materials, components, and manuful Compliance conform to the requirements of Title 24, Part 1 and Part 6 of the California Code The building design features or system design features identified on this Certificate of Compleworksheets, calculations, plans and specifications submitted to the enforcement agency for all will ensure that a registered copy of this Certificate of Compliance shall be made available of all applicable inspections. I understand that a registered copy of this Certificate of Compleworer at occupancy. | of Regulations. iance are consistent with the information provided on other applicable compliance documents, approval with this building permit application. with the building permit(s) issued for the building, and made available to the enforcement agency iance is required to be included with the documentation the builder provides to the building | | | | |
| Responsible Designer Name: Responsible Designer Signature: | | | | | |
| Company: Date Signed: | | | | | |
| Address: | License: | | | | |
| City/State/Zip: | Phone: | | | | |

For assistance or questions regarding the Energy Standards, contact the Energy Hotline at: 1-800-772-3300

| CERTIFICATE OF COMPLIANCE – USER INSTRUCTIONS | CF1R-ALT-01-E |
|---|---------------|
| Prescriptive Residential Alterations | (Page 1 of 4) |

CF1R-ALT-01-E User Instructions

Minimum requirements for prescriptive alteration compliance can be found in Building Energy Efficiency Standards Section 150.2(b)1.

Completing these forms will require that you have the Reference Appendices for the 2016 Building Energy Efficiency Standards. This document contains the Joint Appendices which are used to determine climate zone and to complete the section for opaque surfaces. When the term CF1R is used it means the CF1R-ALT-01.

Instructions for sections with column numbers and row numbers are given separately.

If any part of the alteration does not comply, prescriptive compliance fails, in which case the performance compliance approach must be used in an attempt to achieve compliance.

A. General Information

- 1. Project Name: Identifying information, such as owner's name.
- 2. Date: Date of document preparation.
- 3. Project Location: Legal street address of property or other applicable identifying information.
- 4. Building Front Orientation: Building front expressed in degrees, where North = 0, East = 90, South = 180, and West = 270. Indicate cardinal if it is a subdivision or multi-family project built in multiple orientations. The standards (section 100.1) include the following additional details for determining orientation:
 - Cardinal covers all orientations (for buildings that will be built in multiple orientations);
 - North is oriented to within 45 degrees of true north, including 45 degrees east of north;
 - East is oriented to within 45 degrees of true east, including 45 degrees south of east;
 - South is oriented to within 45 degrees of true south, including 45 degrees west of south;
 - West is oriented to within 45 degrees of true west, including 45 degrees south of west.
- 5. CA City: Legal city/town of property.
- 6. Number of Altered Dwelling Units: 1 for single family, 1 or more for multi-family.
- 7. Zip Code: 5-digit zip code for the project location (used to determine climate zone).
- 8. Fuel Type: Natural Gas, Liquefied Propane Gas, or Electricity.

NOTE: Prescriptive compliance only allows electricity if natural gas is not connected to the building, or if the conditions of Section 150.2(b)1Giic or 150.2(b)1Giid are met. See instruction at section H for more information.

- 9. Climate Zone: From Joint Appendix JA2.1.1.
- 10. Total Conditioned Floor Area: Enter the new conditioned floor area in ft², as measured from the outside of exterior walls of the dwelling unit or building being altered.
- 11. Building Type: Single Family (includes duplex), or Multi-Family (a building that shares common walls and common floors or ceilings).
- 12. Slab Area: Area of the first floor slab (if any) in ft².
- 13. Project Scope: Check all that apply insulation, roof replacement > 50%, space heating system, space cooling system, duct system, water heating, adding fenestration/glazing, replacing fenestration/glazing, adding fenestration/glazing ≤ 75 ft² windows, replacing fenestration/glazing ≤ 75 ft² window, adding fenestration/glazing ≤ 16 ft² skylight and or replacing fenestration/glazing skylights
- 14. Exceptions to Minimum Aged Solar Reflectance and Minimum Thermal Emittance or SRI: No exception, Air-space of 1.0 inch (25mm) is provided between the top of the roof deck to the bottom of the roofing product, the installed roofing product has a profile ratio of rise to width of 1 to 5 for 50 percent or greater of the width of the

| CERTIFICATE OF COMPLIANCE – USER INSTRUCTIONS | CF1R-ALT-01-E |
|---|---------------|
| Prescriptive Residential Alterations | (Page 2 of 4) |

roofing product, existing ducts in the attic are insulated and sealed according to Section 150.1(c)9, building with at least R-38 ceiling insulation, buildings with a radiant barrier in the attic meeting the requirements of Section 150.1(c)2, buildings that have no ducts in attic, R-2 or greater insulation above the roof deck.

B. Roof Replacement (Section 150.2(b)1H)

When 50% or more of the roof is being replaced the roofing requirements are triggered. Any areas of roof covered by building integrated photovoltaic panels and solar thermal panels are exempt; however, the area of roof not covered by photovoltaic panels would still need to meet any applicable cool roof requirements. Additionally, there are many alternatives/exceptions when a cool roof is required.

When the roof is steep slope (pitch greater than 2:12) the roof requirements include a cool roof in climate zones 10-15. The minimum requirement is 0.20 Aged Solar Reflectance, 0.75 Thermal Emittance, or a minimum SRI of 16.

- 1. Tag/ID: A label, if any, from the plans, for example R-1.
- 2. Method of Compliance: Indicate if the method of compliance is going to be based on Aged Solar Reflectance and Thermal Emittance, the Solar Reflectance Index (SRI), or an Exception.
- 3. Roof Pitch: Expressed as 4:12, for example, which means the roof rises 4 feet within a span of 12 feet. When roofs have multiple pitches the requirements are based on the pitch of 50% or more of the roof.
- 4. Exception: If meeting one of the exceptions. Indicate which exception is, or will be, met.

NOTE: Exceptions and alternatives for steep slope roofs:

- (a) Mass roof 25 lbs/ft² or greater (uncommon situation such as sod roof);
- (b) Air space 1" from top of roof deck to bottom of roofing;
- (c) Roofing product has a profile ratio of rise to width of 1 to 5 for 50 percent or greater of the width of the roofing product;
- (d) Ducts already meet Section 150.1(c) insulation and duct leakage requirements;
- (e) Roof has R-38 insulation;
- (f) Roof has a radiant barrier;
- (g) No ducts are installed in the attic; or
- (h) R-2 insulation above the roof deck.

In climate zones 13-15, when there is a low slope roof (pitch 2:12 or less) the cool roof requirements are for a minimum Aged Solar Reflectance of 0.63, a minimum 0.75 Thermal Emittance, or a minimum SRI of 75.

NOTE: Exceptions and alternatives for low slope roofs:

- (a) Mass roof 25 lbs/ft² or greater (uncommon situation such as sod roof);
- (b) No ducts are installed in the attic; or
- (c) Roof deck installation trade off—by installing roof deck insulation, a lower aged solar reflectance is required: R-2 (0.62-0.60), R-4 (0.59-0.55), R-6 (0.54-0.50), R-8 (0.49-0.45), R-12 (0.44-0.40), R-16 (0.39-0.35), R-20 (0.34-0.30), R-24 (0.29-0.25).

NOTE: If one of the exceptions above has been selected than the rest of Section C is Not Required.

5. The CRRC Product ID Number is obtained from the Cool Roof Rating Council's Rated Product Directory at www.coolroofs.org/products/results. Products are listed by CA Building Energy Efficiency Standards - 2016 Residential Compliance

September 2016

(Page 3 of 4)

- manufacturer, brand, type of installation, roofing material, and color, as well as product performance.
- 6. Product Type: See Cool Roof Rating Council's directory. Generally product types include single-ply roof, wood shingles, asphalt roof, metal roof, tile roof.
- 7. R-value Deck Insulation: If one of the exceptions selected includes adding roof deck insulation, indicate the R-value of insulation.
- 8. Proposed Initial Solar Reflectance: Based on the product chosen from the Cool Roof Rating Council's Rated Product Directory. If using default assumption indicate NA since the Aged Solar Reflectance is available.
- 9. Proposed Aged Solar Reflectance: Value is from the Cool Roof Rating Council's Rated Product Directory. If the aged value is not available, calculate the calculated Aged Solar Reflectance using the Solar Reflectance Index (SRI) Calculation worksheet located on the California Energy Commission website (http://energy.ca.gov/title24/2013standards/documents/solar reflectance/) or the aging equation ρ_{aged}=[0.2+β[ρ_{initial}-0.2], where ρ_{initial} = the initial solar reflectance and soiling resistance β is listed by product type below.

| VALUES OF SOILING RESISTANCE β | BY PRODUCT TYPE |
|--------------------------------|-----------------|
|--------------------------------|-----------------|

| Product Type | CRRC Product Category | β |
|-----------------------|-----------------------------|------|
| Field-Applied Coating | Field-Applied Coating | 0.65 |
| Other | Not A Field-Applied Coating | 0.70 |

- 10. Proposed Thermal Emittance: From the product specification default value. If using a calculated SRI place the Thermal Emittance used to calculate SRI.
- 11. Proposed SRI: It is optional to meet the SRI but if chosen to do so, use the Solar Reflectance Index (SRI) Calculation Worksheet found on the California Energy Commission website http://www.energy.ca.gov/title24/2013standards/documents/solar reflectance/.
- 12. Minimum Required Aged Solar Reflectance: Based on climate zone and roof slope.
- 13. Minimum Required Thermal Emittance: Based on climate zone and roof slope.
- 14. Minimum Required SRI: Based on climate zone and roof slope.

NOTE: If the cool roofing requirements will be met by a liquid field applied coating, Section 110.8(i)4 requires the coating be applied across the entire roof surface and meet the dry mil thickness or coverage recommended by the manufacturer.

Signatures

- 1. The person who prepared the CF1R will sign and complete the fields for their name, company (if applicable), address, phone number, certification information (if applicable), date and signature (may be electronic).
- 2. The person who is assuming responsibility for the project being built to comply with Title 24, Part 6, will complete the fields for their name, company (if applicable), address, phone number, license number (if applicable), date and signature (may be electronic).